

Illustra Flex Gen3 3MP & 8MP(4K) Compact Mini-Dome



Key Features

- Easy to install with engineer friendly accessories and WiFi configuration
- Built-in tamper detection for scene change, lens obscuration or blinding light.
- Increased IR Distance
- High speed detection with 60FPS in 2MP resolution
- 3MP & 8MP(4K) resolution provides true HD quality images with video analytics along with improved WDR
- VideoEdge® TrickleStor technology for edge-based failover redundancy
- Advanced analytics (8MP(4K) models only)

High-Quality, Versatile Video Capabilities

The powerful Illustra Flex Compact Mini-Domes are designed to offer a high-image quality, feature rich surveillance option for a wide range of applications. The increased amount of pixels per foot on the 8MP(4K) model improves image detail in wide areas such as loading docks and airport terminals. Also, the Compact Mini-Domes feature built-in IR illuminators to produce clear images at an effective distance in a variety of low light conditions. Deployments that strive for a combination of high-resolution and high-performance at a competitive price point, all while simplifying installation and configuration stand to benefit the most from the these Illustra Compact Mini-Domes.

Powerful Technology to Increase Confidence and Savings

The Flex product family cameras feature built-in technology that ensure efficient recording and smart bandwidth management. When paired with a VideoEdge or exacqVision NVR, edge-based failover redundancy allows video recording to continue on the camera when when a network disruption occurs or the NVR is offline, then when connection is restored transfers video back to the media database for seamless viewing later. Illustra® IntelliZip continuously monitors and optimizes system streaming parameters to match the level of activity within the camera's field of view.

Safeguard Against Cyber Attacks Across Devices

Illustra Flex Cameras have been designed to be resilient against cyber-threats. Our products are gated, analyzed, tested and required to meet or exceed the rigorous standards of the Johnson Controls Cyber Solutions Product Security Program for every consecutive release. This holistic approach is aimed at providing peace of mind to our customers. Our security mindset begins at initial design concept and is supported through deployment, including a rapid incident response to meet the comprehensive and evolving cybersecurity environments.

Specifications

Operational	3MP	8MP(4K)
Video Compression	MJPEG, H.264, H.264 IntelliZip, H.265 and H.265 IntelliZip	
Resolution	2048x1536/ 1920x1080/ 1664x936/ 1280x720/ 1024x576/ 640x480/ 640x360/ 480x360/ 384x288	3840x2160/ 3264x1840/ 2688x1520/ 1920x1080/ 1664x936/ 1280x720/ 1024x576/ 960x544/ 816x464/ 640x360/ 480x272
Max. Framerate	H.265/H.264: Max. 60fps MJPEG: Max. 20fps	
Smart Codec	IntelliZip	
Imaging Device	1/2.8" 3.21MP CMOS	1/1.8" 8.3MP CMOS
Effective Pixels	2065(H) x 1553(V)	3840(H) x 2160(V)
Min. Illumination	Color: min 0.05 lux (1/30sec, 30IRE) BW: 0.005Lux	Color: min 0.27 lux (1/30sec, 30IRE) BW: 0.027Lux
Focal Length	2.8mm fixed focal	4.27mm fixed focal
Max. Aperture Ratio	F2.0	F1.6
Angular Field of View	H: 100.13° V: 73.79° D: 128°	H: 107.97° V: 58.02° D: 126.87°
Focus Control	Fixed (peak focus at 5m)	
Lens Type	None	
IR Viewable Length	15m (49.21ft) including smart IR control	
Day & Night	Auto Low/ Auto Mid(Default)/ Auto High/ Manual/ Forced Color/ Force B&W	
Backlight Compensation	Exposure Weighting: Top, Bottom, Left, Right, Full, Centre, Spot	
Wide Dynamic Range	True WDR 140db Technologies	True WDR 120db Technologies
Digital Noise Reduction	2D&3DNR	
Signal to Noise Ratio (SNR)	50db	
Digital Image Stabilization	No	
Motion Detection	3ea, polygonal zones	
Privacy Masking	9ea, rectangular zones	
Gain Control	Automatic & Manual (3dB increments)	
White Balance	Automatic Wide, Automatic Normal, Manual	
Lens Distortion Correction	Support	
Electronic Shutter Speed	Minimum 1/4s, Maximum 1/10,000s	
Video Rotation	Corridor Mode, Mirror & Flip	
Alarm I/O	No	
Alarm Triggers	Motion detection, Tampering detection, Defocus detection	
Alarm Events	Onboard recording, snapshot, Notification via e-mail, FTP upload, CIFS upload	
Micro USB	WiFi Installation Support via Illustra Mobile Toolkit	
Pan / Tilt / Rotate		
Pan / Tilt / Rotate Range	0°~350° / 0°~67° / 0°~355°	







Video Intelligence Analytics		
Standard	Tampering, Defocus / Motion Detection	
Advanced ¹	-	Linger, Exit, Direction, Abandoned/ Removed Objects, Dwell, Enter, Object Detection, Perimeter, Queue, Crowd
Face Detection ¹	-	Yes
Tamper Detection	Scene Change	
Blur Detection	Yes	
Network		
Ethernet	RJ-45(10/100BASE-T)	RJ-45(10/100/1000BASE-T)
Bitrate Control	H.264/H.265: CBR or VBR or CVBR	
Streaming	Multiple streaming (Up to 3 profiles)	
Audio Compression	G.711 alaw and ulaw selectable G.711 8KHz	
Protocol	TCP/IP, IPv4, IPv6, TCP, UDP, HTTP, FTP, DHCP, WS-Discovery, DNS, DDNS, RTP, RTCP, RTSP, TLS, Unicast, Multicast, NTP, ICMP, IGMP, SMTP, WS-Security, IEEE 802.1x, PEAP, EAP-TLS, EAPoL, SSH, HTTPS, SOAP, WSAddressing, CIFS, SNMP, UPNP, RTSP, LLDP	
Security	TLS - RFC5246 v1.2, HTTPS (HTTP over TLS) - RFC2818, WS-Security, Certificate Management, Multi-Level Password Protection, IP Address/ Filtering, HTTPS Encryption, One-Click Security Hardening, User Access Log, Validate Complex Credentials, Disabling Unused Protocols, IEEE / 802.1x Including: PEAP, EAP-TLS, EAPoL	
Edge Storage	Micro SD/SDHC/SDXC 1slot 512GB	
Application Programming Interface	iAPI-3	
ONVIF-Compliant	Profile S	
Memory	512MB RAM, 512MB Flash	1GB RAM, 512MB Flash
Environmental		
Operating Temperature / Humidity	-40°C ~ +50°C (-40°F ~ +122°F) / Less than 90% RH	
Storage Temperature / Humidity	-40°C ~ +55°F (-40°C ~ +131°F) / Less than 90% RH	
Environmental	IP66/ IP67	
Vandal Resistance	IK10	
Electrical		
Input Voltage	PoE 802.3af (802.3at Type 1)	
Power Consumption	PoE: Max 8.1W	PoE: Max 10.1W
Mechanical		
Color / Material	White / Aluminum	
RAL Code	RAL9003	
Product dimensions / weight	112 x 72 mm (4.41 x 2.83 in)	
Regulatory		
Safety	UL62368-1; CAN/CSA-C22.2 No. 62368-1, BIS IS13252 Part 1:2010	
Emissions	FCC Part 15 Class A; EN55032 Class A; AS/NZS CISPR 32 Class A; ICES-003/NMB-003 Class A	
Immunity	EN50130-4	
Environment	RoHS/WEEE, REACH	

1. Advanced Analytics and Face Detection subject to future firmware release

Ordering information

Model Number	Description
IFS03-C10-OI03	Illustra Flex 3MP Gen3 Compact, 2.8mm Fixed, IP66/67 IK10, TDN w/IR, WDR
IFS08-C10-OI03	Illustra Flex 4K Gen3 Compact, 4.27mm Fixed, IP66/67 IK10, TDN w/IR, WDR

Accessories

Model Number		Description
IBJB-F-3CWB-0		Illustra Flex Gen3 Compact Junction Box for Flex Gen3 Compact Domes
ADCi6DPCAPOW		Pendant Cap, White
ADLOMARM		Gooseneck Mounting Arm, White
ADCDMCRNRO		Corner Mount Adapter, White
ADCDMPOLE		Pole Mount Adapter, White
ADCiM6WALLWK		Wall Mount, White

Specifications are subject to amendment without notification

About Johnson Controls

Johnson Controls is a global diversified technology and multi-industrial leader serving a wide range of customers in more than 150 countries. Our 120,000 employees create intelligent buildings, efficient energy solutions, integrated infrastructure and next generation transportation systems that work seamlessly together to deliver on the promise of smart cities and communities. Our commitment to sustainability dates back to our roots in 1885, with the invention of the first electric room thermostat.

For additional information, please visit www.illustracameras.com follow us on Facebook, Twitter, and LinkedIn.